

Give your gear extra space. With a deeper lid, the iM2275 is the first case in our Pelican™ Storm Case™ line that gives you more vertical space to work with for your equipment. This case gives you the freedom to configure multiple 4K cameras, diagnostic circuit readers, or a drone with accessories.

- Two Press & Pull Latches
- Lightweight Strong HPX® Resin
- Watertight, crushproof, and dustproof
- Vortex™ Valve
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Powerful Hinges
- Guaranteed for life

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	14.12 x 13.19 x 9.90 in
Interior (L×W×D) - Centimeters	35.86 x 33.5 x 25.15 cm
Exterior (L×W×D) - Inches	15.25 x 15.50 x 10.22 in
Exterior (L×W×D) - Centimeters	38.74 x 39.37 x 25.96 cm
Padlock Hole Diameter	0.37 in

CAPACITY

Lid Depth	3.20 in (8.13 cm)
Bottom Depth	6.30 in (16 cm)
Buoyancy	68.80 lbs

WEIGHTS

Weight With Foam	10.25 lbs (4.65 kg)
Weight No Foam	8.00 lbs (3.63 kg)

TEMPERATURE RANGE

Minimum Temperature	-20°F (-28.9°C)
Maximum Temperature	140°F (60°C)

MATERIALS

Body Material	Injection Molded HPX™ high performance resin
Latch Material	Valox - Polybutylene Terephthalate (PBT)
Latch Alt Material	Xenoy - Polyester/Polycarbonate blend
O Ring Material	EPDM
Pins Material	Stainless Steel
Pins Alt Material	Aluminum
Foam Material	1.3/1.35 polyester
Purge Body Material	Valox - Polybutylene Terephthalate (PBT)
Purge Body Alt Material	Xenoy - Polyester/Polycarbonate blend
Purge Vent Material	Gortex membrane
Purge O Ring Material	Buna-N, 50-60 Durometer Shore A