

Pelican™ 3345 VLO with Variable Light Output: The first pro-grade torch that automatically adjusts brightness.

It has a mind of its own. The Variable Light Output sensor (VLO) in the new Pelican™ 3345 VLO examines the ambient light/proximity and instantly adjusts its lumens to the most effective level. Now you can read pressure gauges close up or throw light hundreds of meters away - without hassling over manual power settings.

The Variable Light Output sensor also makes the Pelican™ 3345 VLO one of our most energy efficient torches, preserving power and stretching battery life. Plus, the secondary flood beam illuminates potential trip hazards like loose cables, while the primary spot beam brightens long tunnels.

The integrated clip can be mounted to a safety vest for hands free lighting.

With Class I, II, III, Division 1 /IECEX ia certifications and a full time battery level indicator, you can work in hazardous areas around the globe.

- Full Time Battery Level Indication
- Variable Light Output (automatically adjust to ambient light levels and proximity)
- Dual Beams (Spot and Flood)
- Safety Certified, Class I, II, III, Division 1/IECEX ia
- Integrated Clip
- 3 AA Alkaline Batteries (not included)

SPECS

SIZES

Length	7.25 in (18.4 cm)
--------	-------------------

LIGHT SPECIFICATIONS

Lamp Type	LED
-----------	-----

POWER

Rechargeable	No
Battery Quantity	3
Battery Size	AA
Batteries Included	No
Volts	4.5 V
Battery Type	Alkaline
Battery Level Indicator	Full-time battery indicator

SWITCH & MODES

Light Modes	High
Switch Type	Push Button

WEIGHT

Weight With Batteries	7.5 oz (212.62 g)
Weight No Batteries	5.0 oz (141.75 g)
Weight	0.43 oz (12.19 g)

MATERIALS

Body Material	ABS
Shroud Material	ABS
Lens Material	Polycarbonate (PC)
Clip Material	ABS
O Ring Material	NBR