

472-PWC-M60



Mobile Armory Mobile Military

472-PWC-M60

- Six Press & Pull Latches
- Watertight
- In-line Wheels
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Vortex™ Valve
- Lightweight Strong HPX™ Resin
- Powerful Hinges
- Guaranteed For Life

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	50.50 x 14.00 x 6.00 in
Interior (L×W×D) - Centimeters	128.27 x 35.56 x 15.24 cm
Exterior (L×W×D) - Inches	53.80 x 16.50 x 6.70 in
Exterior (L×W×D) - Centimeters	136.65 x 41.91 x 17.02 cm

CAPACITY

Lid Depth	2.00 in (5.08 cm)
Bottom Depth	4.00 in (10.16 cm)

WEIGHTS

Weight	23.00 lbs (10.43 kg)
--------	----------------------

TEMPERATURE RANGE

Minimum Temperature	-20°F (-28.9°C)
Maximum Temperature	140°F (60°C)

MATERIALS

Body Material	Injection Molded HPX™ high performance resin
Latch Material	Valox - Polybutylene Terephthalate (PBT)
Latch Alt Material	Xenoy - Polyester/Polycarbonate blend
O Ring Material	Silicone Sponge
Pins Material	Stainless Steel
Foam Material	1.3/1.35 polyester
Purge Body Material	Valox - Polybutylene Terephthalate (PBT)
Purge Body Alt Material	Xenoy - Polyester/Polycarbonate blend
Purge Vent Material	Gortex membrane
Purge O Ring Material	Buna-N, 50-60 Durometer Shore A