

472-PWC-M9-12



Mobile Armory Mobile Military

- Five Press & Pull Latches
- Watertight
- Telescoping Handle
- In-line Wheels
- Two Padlockable Hasps
- Three Double-layered, Soft-grip Handles
- Vortex™ Valve
- Flush Powerful Hinges
- Lightweight Strong HPX™ Resin
- Guaranteed For Life

472-PWC-M9-12

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	29.00 x 18.00 x 10.50 in
Interior (L×W×D) - Centimeters	73.66 x 45.72 x 26.67 cm
Exterior (L×W×D) - Inches	31.30 x 20.40 x 12.20 in
Exterior (L×W×D) - Centimeters	79.5 x 51.82 x 30.99 cm

CAPACITY

Lid Depth	2.00 in (5.08 cm)
Bottom Depth	8.50 in (21.59 cm)

WEIGHTS

Weight	28.70 lbs (13.02 kg)
--------	----------------------

TEMPERATURE RANGE

Minimum Temperature	-20°F (-28.9°C)
Maximum Temperature	140°F (60°C)

MATERIALS

Body Material	Injection Molded HPX™ high performance resin
Latch Material	Valox - Polybutylene Terephthalate (PBT)
Latch Alt Material	Xenoy - Polyester/Polycarbonate blend
O Ring Material	Silicone Sponge
Pins Material	Stainless Steel
Foam Material	1.3/1.35 polyester
Purge Body Material	Valox - Polybutylene Terephthalate (PBT)
Purge Body Alt Material	Xenoy - Polyester/Polycarbonate blend
Purge Vent Material	Gortex membrane
Purge O Ring Material	Buna-N, 50-60 Durometer Shore A