

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- 1550 Case customized for EMS personnel
- Multi layer lid organizer with numerous clean pockets - find everything right away
- Padded dividers with adjustable walls for customizing compartments to any size.
- Lid organizer clear cover with VELCRO® brand fasteners - keep supplies in place during transport
- Watertight, crushproof, and dustproof
- Stainless steel padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law
- CONTENTS NOT INCLUDED
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 18.43 x 14.00 x 7.62 in  |
| Interior (L×W×D) - Centimeters | 46.81 x 35.56 x 19.35 cm |
| Exterior (L×W×D) - Inches      | 20.62 x 16.87 x 8.12 in  |
| Exterior (L×W×D) - Centimeters | 52.37 x 42.85 x 20.62 cm |
| Padlock Hole Diameter          | 5/16 in                  |

CAPACITY

|              |                    |
|--------------|--------------------|
| Lid Depth    | 1.75 in (4.45 cm)  |
| Bottom Depth | 5.87 in (14.91 cm) |
| Buoyancy     | 69.89 lbs          |

WEIGHTS

|                    |                    |
|--------------------|--------------------|
| Weight With Foam   | 15.00 lbs (6.8 kg) |
| Master Pack Weight | 15.00 lbs (6.8 kg) |
| Weight             | 15.1 lbs (6.85 kg) |

TEMPERATURE RANGE

|                     |                |
|---------------------|----------------|
| Minimum Temperature | -40°F (-40°C)  |
| Maximum Temperature | 190°F (87.8°C) |

MATERIALS

|                       |                                |
|-----------------------|--------------------------------|
| Body Material         | Polypropylene                  |
| Latch Material        | ABS                            |
| O Ring Material       | Polymer                        |
| Pins Material         | Stainless Steel                |
| Foam Material         | 1.3 lb Polyurethane            |
| Purge Body Material   | ABS                            |
| Purge Vent Material   | 3 Micron Hydrophobic Non-Woven |
| Purge O Ring Material | 70 Shore Nitrile               |