

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- 4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- Water resistant, crushproof, and dust resistant
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Easy open double-throw latches
- Fold down handles
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Personalized nameplate service available

SPECS

MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 21.48 x 16.42 x 12.54 in |
| Interior (L×W×D) - Centimeters | 54.56 x 41.71 x 31.85 cm |
| Exterior (L×W×D) - Inches      | 26.20 x 23.00 x 15.61 in |
| Exterior (L×W×D) - Centimeters | 66.55 x 58.42 x 39.65 cm |
| Padlock Hole Diameter          | 5/16 in                  |

CAPACITY

|              |                     |
|--------------|---------------------|
| Lid Depth    | 2.01 in (5.11 cm)   |
| Bottom Depth | 10.53 in (26.75 cm) |

WEIGHTS

|                  |                      |
|------------------|----------------------|
| Weight With Foam | 31.42 lbs (14.25 kg) |
| Weight No Foam   | 28.00 lbs (12.7 kg)  |
| Weight           | 36.85 lbs (16.71 kg) |

## TEMPERATURE RANGE

|                     |                |
|---------------------|----------------|
| Minimum Temperature | -40°F (-40°C)  |
| Maximum Temperature | 190°F (87.8°C) |

## MATERIALS

|                       |                                |
|-----------------------|--------------------------------|
| Body Material         | Polypropylene                  |
| Latch Material        | ABS                            |
| O Ring Material       | Polymer                        |
| Pins Material         | Stainless Steel                |
| Foam Material         | 1.3 lb Polyurethane            |
| Purge Body Material   | ABS                            |
| Purge Vent Material   | 3 Micron Hydrophobic Non-Woven |
| Purge O Ring Material | 70 Shore Nitrile               |