

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- 4 strong polyurethane wheels with stainless steel bearings
- Two oversized fold down handles for extra grip
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck™ with convoluted lid foam
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Easy open double-throw latches
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Peli's legendary lifetime guarantee**
- O-ring seal
- * Where applicable by law
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	28.10 x 16.49 x 9.19 in
Interior (L×W×D) - Centimeters	71.37 x 41.88 x 23.34 cm
Exterior (L×W×D) - Inches	31.04 x 19.39 x 11.17 in
Exterior (L×W×D) - Centimeters	78.84 x 49.25 x 28.37 cm
Padlock Hole Diameter	0.31 in

CAPACITY

Lid Depth	1.80 in (4.57 cm)
Bottom Depth	7.39 in (18.77 cm)
Buoyancy	182.00 lbs

WEIGHTS

Weight With Foam	26.00 lbs (11.79 kg)
Weight No Foam	23.00 lbs (10.43 kg)
Master Pack Weight	49.00 lbs (22.23 kg)
Weight	28.5 lbs (12.93 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	ABS
O Ring Material	Polymer
Pins Material	Stainless Steel
Foam Material	1.3 lb Polyurethane
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile