

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Four extra-deep base-to-lid locking cleats that ensure maximum stacking stability
- 4-piece foam set
- Wide-track polyurethane wheels with ball bearings and nylon hubs
- Watertight, crushproof, and dustproof
- Open cell core, polymer wall construction
- Two Integrated Automatic Pressure Equalization Valves
- Two rugged double-wide handles
- Comfortable rubber over-molded side-carry handle
- Stainless steel hardware and padlock protectors
- O-ring seal
- Also available from Pelican: The 1740 Long Case
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	54.58 x 15.58 x 8.63 in
Interior (L×W×D) - Centimeters	138.63 x 39.57 x 21.92 cm
Exterior (L×W×D) - Inches	57.42 x 18.48 x 10.50 in
Exterior (L×W×D) - Centimeters	145.85 x 46.94 x 26.67 cm
Padlock Hole Diameter	0.31 in

CAPACITY

Lid Depth	1.65 in (4.19 cm)
Bottom Depth	6.75 in (17.15 cm)
Buoyancy	280.00 lbs

WEIGHTS

Weight With Foam	41.49 lbs (18.82 kg)
Weight No Foam	36.01 lbs (16.33 kg)
Master Pack Weight	39.50 lbs (17.92 kg)
Weight	43.25 lbs (19.62 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	ABS
O Ring Material	EPDM
Pins Material	Stainless Steel
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile