

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- The new class of XXL Pelican Transport Cases
- 50/50 lid-to-base ratio for easy loading
- Watertight, crushproof, and dustproof
- 4 strong polyurethane wheels with stainless steel bearings
- Completely detachable lid for full access
- Easy open double-throw latches
- Open cell core with solid wall design - strong, light weight
- Fold down handles
- Stainless steel padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Peli's legendary lifetime guarantee**
- O-ring seal
- * Where applicable by law
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	41.12 x 21.54 x 14.88 in
Interior (L×W×D) - Centimeters	104.44 x 54.71 x 37.8 cm
Exterior (L×W×D) - Inches	44.90 x 25.32 x 16.50 in
Exterior (L×W×D) - Centimeters	114.05 x 64.31 x 41.91 cm
Padlock Hole Diameter	0.31 in

CAPACITY

Lid Depth	7.58 in (19.25 cm)
Bottom Depth	7.30 in (18.54 cm)
Buoyancy	500.00 lbs

WEIGHTS

Weight With Foam	49.00 lbs (22.23 kg)
Weight No Foam	38.40 lbs (17.42 kg)
Master Pack Weight	56.00 lbs (25.4 kg)
Weight	56.6 lbs (25.67 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	EXL
O Ring Material	Polymer
Pins Material	Stainless Steel
Foam Material	1.3 lb Polyurethane
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile