

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Two Press & Pull Latches
- Lightweight Strong HPX® Resin
- Watertight, crushproof, and dustproof
- In-line Wheels
- Two stainless steel padlock protectors
- Retractable extension trolley handle
- O-ring seal
- Guaranteed for life

## SPECS

### MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 17.50 x 6.50 x 15.50 in  |
| Interior (L×W×D) - Centimeters | 44.45 x 16.51 x 39.37 cm |
| Exterior (L×W×D) - Inches      | 18.63 x 9.25 x 16.50 in  |
| Exterior (L×W×D) - Centimeters | 47.32 x 23.5 x 41.91 cm  |
| Padlock Hole Diameter          | 0.37 in                  |

### CAPACITY

|              |                     |
|--------------|---------------------|
| Lid Depth    | 2.00 in (5.08 cm)   |
| Bottom Depth | 13.50 in (34.29 cm) |
| Buoyancy     | 56.70 lbs           |

### WEIGHTS

|                  |                     |
|------------------|---------------------|
| Weight With Foam | 11.15 lbs (5.06 kg) |
| Weight No Foam   | 10.00 lbs (4.54 kg) |

### TEMPERATURE RANGE

|                     |                 |
|---------------------|-----------------|
| Minimum Temperature | -20°F (-28.9°C) |
| Maximum Temperature | 140°F (60°C)    |

# MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| Body Material           | Injection Molded HPX™ high performance resin |
| Latch Material          | Valox - Polybutylene Terephthalate (PBT)     |
| Latch Alt Material      | Xenoy - Polyester/Polycarbonate blend        |
| O Ring Material         | EPDM                                         |
| Pins Material           | Stainless Steel                              |
| Pins Alt Material       | Aluminum                                     |
| Foam Material           | 1.3/1.35 polyester                           |
| Purge Body Material     | Valox - Polybutylene Terephthalate (PBT)     |
| Purge Body Alt Material | Xenoy - Polyester/Polycarbonate blend        |
| Purge Vent Material     | Gortex membrane                              |
| Purge O Ring Material   | Buna-N, 50-60 Durometer Shore A              |