

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

## SPECS

### MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 22.00 x 17.00 x 10.00 in |
| Interior (L×W×D) - Centimeters | 55.88 x 43.18 x 25.4 cm  |
| Exterior (L×W×D) - Inches      | 24.60 x 19.70 x 11.70 in |
| Exterior (L×W×D) - Centimeters | 62.48 x 50.04 x 29.72 cm |
| Padlock Hole Diameter          | 0.31 in                  |

### CAPACITY

|              |                    |
|--------------|--------------------|
| Lid Depth    | 2.00 in (5.08 cm)  |
| Bottom Depth | 8.00 in (20.32 cm) |
| Buoyancy     | 138.14 lbs         |

### WEIGHTS

|                    |                      |
|--------------------|----------------------|
| Weight With Foam   | 22.00 lbs (9.98 kg)  |
| Weight No Foam     | 16.80 lbs (7.62 kg)  |
| Master Pack Weight | 24.00 lbs (10.89 kg) |
| Weight             | 19 lbs (8.62 kg)     |

### TEMPERATURE RANGE

|                     |                 |
|---------------------|-----------------|
| Minimum Temperature | -20°F (-28.9°C) |
| Maximum Temperature | 140°F (60°C)    |

## MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| Body Material           | Injection Molded HPX™ high performance resin |
| Latch Material          | Valox - Polybutylene Terephthalate (PBT)     |
| Latch Alt Material      | Xenoy - Polyester/Polycarbonate blend        |
| O Ring Material         | EPDM                                         |
| Pins Material           | Stainless Steel                              |
| Pins Alt Material       | Aluminum                                     |
| Foam Material           | 1.3/1.35 polyester                           |
| Purge Body Material     | Valox - Polybutylene Terephthalate (PBT)     |
| Purge Body Alt Material | Xenoy - Polyester/Polycarbonate blend        |
| Purge Vent Material     | Gortex membrane                              |
| Purge O Ring Material   | Buna-N, 50-60 Durometer Shore A              |