

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Six Press & Pull Latches
- Lightweight Strong HPX® Resin
- Two Double-layered, Soft-grip Handles
- Vortex™ Valve
- Two Padlockable Hasps
- Powerful Hinges
- O-ring seal
- Guaranteed For Life

## SPECS

### MEASUREMENTS

|                                |                           |
|--------------------------------|---------------------------|
| Interior (L×W×D) - Inches      | 44.00 x 14.00 x 6.00 in   |
| Interior (L×W×D) - Centimeters | 111.76 x 35.56 x 15.24 cm |
| Exterior (L×W×D) - Inches      | 47.20 x 16.50 x 6.70 in   |
| Exterior (L×W×D) - Centimeters | 119.89 x 41.91 x 17.02 cm |
| Padlock Hole Diameter          | 0.38 in                   |

### CAPACITY

|              |                    |
|--------------|--------------------|
| Lid Depth    | 2.00 in (5.08 cm)  |
| Bottom Depth | 4.00 in (10.16 cm) |
| Buoyancy     | 136.09 lbs         |

### WEIGHTS

|                    |                     |
|--------------------|---------------------|
| Weight With Foam   | 21.10 lbs (9.57 kg) |
| Weight No Foam     | 17.70 lbs (8.03 kg) |
| Master Pack Weight | 19.70 lbs (8.94 kg) |

### TEMPERATURE RANGE

|                     |                 |
|---------------------|-----------------|
| Minimum Temperature | -20°F (-28.9°C) |
| Maximum Temperature | 140°F (60°C)    |

MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| Body Material           | Injection Molded HPX™ high performance resin |
| Latch Material          | Valox - Polybutylene Terephthalate (PBT)     |
| Latch Alt Material      | Xenoy - Polyester/Polycarbonate blend        |
| O Ring Material         | EPDM                                         |
| Pins Material           | Stainless Steel                              |
| Pins Alt Material       | Aluminum                                     |
| Foam Material           | 1.3/1.35 polyester                           |
| Purge Body Material     | Valox - Polybutylene Terephthalate (PBT)     |
| Purge Body Alt Material | Xenoy - Polyester/Polycarbonate blend        |
| Purge Vent Material     | Gortex membrane                              |
| Purge O Ring Material   | Buna-N, 50-60 Durometer Shore A              |