

472-PWC-M9-2



Mobile Armory Mobile Military

472-PWC-M9-2

- Meets Carry-on Regulations
- Watertight
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Flush Powerful Hinges
- Lightweight Strong HPX™ Resin
- Guaranteed For Life

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	15.00 x 10.50 x 6.00 in
Interior (L×W×D) - Centimeters	38.1 x 26.67 x 15.24 cm
Exterior (L×W×D) - Inches	16.20 x 12.70 x 6.60 in
Exterior (L×W×D) - Centimeters	41.15 x 32.26 x 16.76 cm

CAPACITY

Lid Depth	2.00 in (5.08 cm)
Bottom Depth	4.00 in (10.16 cm)

WEIGHTS

Weight	6.10 lbs (2.77 kg)
--------	--------------------

TEMPERATURE RANGE

Minimum Temperature	-20°F (-28.9°C)
Maximum Temperature	140°F (60°C)

MATERIALS

Body Material	Injection Molded HPX™ high performance resin
Latch Material	Valox - Polybutylene Terephthalate (PBT)
Latch Alt Material	Xenoy - Polyester/Polycarbonate blend
O Ring Material	Silicone Sponge
Pins Material	Stainless Steel
Foam Material	1.3/1.35 polyester
Purge Body Material	Valox - Polybutylene Terephthalate (PBT)
Purge Body Alt Material	Xenoy - Polyester/Polycarbonate blend
Purge Vent Material	Gortex membrane
Purge O Ring Material	Buna-N, 50-60 Durometer Shore A