

SPECS

MEASUREMENTS

|                                |                           |
|--------------------------------|---------------------------|
| Interior (L×W×D) - Inches      | 50.50 x 14.00 x 6.00 in   |
| Interior (L×W×D) - Centimeters | 128.27 x 35.56 x 15.24 cm |
| Exterior (L×W×D) - Inches      | 53.80 x 16.50 x 6.70 in   |
| Exterior (L×W×D) - Centimeters | 136.65 x 41.91 x 17.02 cm |

CAPACITY

|              |                    |
|--------------|--------------------|
| Lid Depth    | 2.00 in (5.08 cm)  |
| Bottom Depth | 4.00 in (10.16 cm) |

WEIGHTS

|        |                      |
|--------|----------------------|
| Weight | 23.00 lbs (10.43 kg) |
|--------|----------------------|

TEMPERATURE RANGE

|                     |                 |
|---------------------|-----------------|
| Minimum Temperature | -20°F (-28.9°C) |
| Maximum Temperature | 140°F (60°C)    |

MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| Body Material           | Injection Molded HPX™ high performance resin |
| Latch Material          | Valox - Polybutylene Terephthalate (PBT)     |
| Latch Alt Material      | Xenoy - Polyester/Polycarbonate blend        |
| O Ring Material         | Silicone Sponge                              |
| Pins Material           | Stainless Steel                              |
| Foam Material           | 1.3/1.35 polyester                           |
| Purge Body Material     | Valox - Polybutylene Terephthalate (PBT)     |
| Purge Body Alt Material | Xenoy - Polyester/Polycarbonate blend        |
| Purge Vent Material     | Gortex membrane                              |
| Purge O Ring Material   | Buna-N, 50-60 Durometer Shore A              |